

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



10/532619



(43) International Publication Date  
13 May 2004 (13.05.2004)


PCT

(10) International Publication Number  
WO 2004/040897 A2

- (51) International Patent Classification<sup>7</sup>: H04N
- (21) International Application Number: PCT/US2003/032800
- (22) International Filing Date: 16 October 2003 (16.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/421,288 25 October 2002 (25.10.2002) US
- (63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:  
US 90/844,401 (CIP)  
Filed on 27 April 2001 (27.04.2001)
- (71) Applicant (for all designated States except US): THE DIRECTV GROUP, INC. [US/US]; 2250 E. Imperial Highway, El Segundo, CA 90245 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CHEN, Ernest, C. [US/US]; 1025 Via Cordova, San Pedro, CA 90732 (US).
- (74) Agents: CROOK, John, A. et al.; Hughes Electronics Corporation, Patent Docket Department, RE/R11/A109, P.O. Box 956, El Segundo, CA 90245-0956 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: MAXIMIZING POWER AND SPECTRAL EFFICIENCIES FOR LAYERED AND CONVENTIONAL MODULATIONS



(57) Abstract: Methods and apparatuses for maximizing power and spectral efficiencies in a wireless communication system are disclosed. The invention is particularly useful for layered modulation applications because power levels for such applications are relatively high. A layered modulation signal comprises an upper and a lower layer signal that interfere with each other within the same frequency band such that the upper layer signal can be demodulated directly from the layered modulation signal, and the lower layer signal can be demodulated after subtracting the first layer signal from the layered modulation signal. The invention applies one or more of the following four signal schemes in a communication signal including varying the symbol rate (rather than the code rate), reducing or eliminating the guard band, reducing excess signal bandwidth and employing layered modulation within the guard band of the legacy signal.